



DURASCRIM
POLYESTER REINFORCING FABRIC FOR USE WITH DURAM MEMBRANES AND COATINGS

DESCRIPTION

Open weave polyester reinforcing fabric for the use of reinforcing Duram waterproofing membranes.

Available in the following roll sizes:

- 150mm x 10m
- 100mm x 50m
- 150mm x 50m
- 1.2m x 50m

USES

As a reinforcing fabric, **Duram Durascrim** is suitable to use with the following Duram Membranes: **Durabit EF, Durabit REO, Durabit-Bitumen Free, Azcoflex, Pondseal, Duram 195 and Multithane Range.**

Reinforcing membranes with **Durascrim** is recommended over joins, cracks, gaps and in corners or wherever additional tensile strength or membrane build up is desired.

Refer to product data sheet for the particular Duram waterproofing product.

SPECIFICATION

The information contained in this product data sheet is typical but does not constitute a full specification as conditions and specific requirements may vary from project to project. The instructions should be considered as a minimum requirement, but the applicator or contractor must use their skill, knowledge and experience to carry out additional works as may be necessary to meet the requirements of the project. Specification for specific projects should be sought from the Company in writing.

BENEFITS AND ADVANTAGES

By using **Durascrim**:

- Provides additional strength to waterproofing membranes.
- Allows greater product build up.

APPLICATION SUGGESTION WHEN USING DURASCRIM

Apply 1st coat of the Duram membrane, usually at no less than 500 microns thick, and embed the **Durascrim** into wet coat. Apply a similar saturating coat over and working it in to the **Durascrim** ensuring that there are no wrinkles, folds or bubbles in fabric and sufficient product has been applied to cover the fabric. Allow to dry. Apply 1 to 2 additional coats at 500 microns thick and allow to dry.

Refer to product data sheets of the Duram membrane in question.

COVERAGE

The stated average coverage rate may vary depending upon type, condition, porosity, texture of the surface and application technique.

Generally, at least 2 Lt per m² of product is needed to properly saturate and cover **Durascrim**.

COLOURS

Durascrim comes in white

STORAGE

Store in dry area.

SAFETY AND PRECAUTIONS

For full safety data refer to the products Safety Data Sheet. Observe precautions as per label.

CONDITIONS OF USE AND DISCLAIMER

The information contained in this TDS is given in good faith based upon our current knowledge and does not imply warranty, express or implied. The information is provided, and the product is sold on the basis that the product is used for its intended purpose and is used in a proper workmanlike manner in accordance with the instructions of the TDS in suitable and safe working conditions. Under no circumstances will the Company be liable for loss, consequential or otherwise, arising from the use of the product.

Version: 001-122020

DURAM ABN 25 000 024 064

A DIVISION OF TREMCO CPG AUSTRALIA PTY LTD

The Ultimate in Waterproofing & Protective Coating Technology

Duram Offices:

NEW SOUTH WALES:	51 Prince William Drive, Seven Hills, NSW 2147	Tel (02) 9624 4077 Fax: (02) 9624 4079
QUEENSLAND:	63 Radley Street, Virginia, QLD 4014	Tel (07) 3255 6478 Fax: (07) 3255 6258