

Technical Data Sheet ISSUED AUGUST 2023

PRODUCT DESCRIPTION

WPA 360 is a water based, low solids, fast drying primer used in conjunction with our range of water-based membranes including WPA 200, WPA 230UV, WPA 400, WPA 500 or WPA Rapid waterproofing membranes.

The application of WPA 360 aids in providing a substrate with uniform absorption and enhances adhesion of subsequent coatings.

FEATURES AND BENEFITS

- Solvent free;
- Non-hazardous;
- Fast drying;
- Good adhesion properties;
- Economical.

RECOMMENDED FOR:

- Internal Wet Area
- Balconies
- Decks

APPLICATION PROCEDURE

Substrates

Suitable for:

- Concrete, render, screed, block work, fibre cement sheeting, wet area plasterboard.

Preparation

All surfaces to be coated must be firm, clean, dry, sound and smooth. All laitance, grease, oil, wax, curing compounds, loose material, paint and any other contaminants which may reduce or prevent adhesion must be mechanically removed. Masonry surfaces must be pointed flush and surface defects repaired. New concrete must be cured for a minimum of 28 days.

Fibre cement sheeting and water resistant plasterboard must be installed in accordance with the manufacturers' installation requirements.

Application

Stir the contents thoroughly prior to application. Apply WPA 360 by brush, roller (short nap) to obtain a consistent and even coating. Apply a second coat on highly porous substrates if required. Allow the first coat to fully dry before applying the second coat of WPA 360 if required. WPA 360 must be applied at a minimum coverage of 1 litre/10m².

Allow a minimum of 30 minutes before over coating with the selected waterproofing membrane. Allow longer drying times in cool, damp or higher humidity conditions.

Performance Data and Physical Properties @23°C & 55% RH

- Colour: Red (when cured)
- Membrane Application: As soon as primer is touch dry.
- Flash Point: Not applicable.
- Coverage: 10 m² per litre. (Depending on application method and substrate porosity).

LIMITATIONS

Do not apply WPA 360:

- In areas subject to rising damp;
- If it is raining or rain is imminent;
- As a primer for trafficable membranes. Use WPA 460 or WPA 560;
- On non-porous substrates. Use WPA 160;

Clean Up

Clean brushes, roller sleeves and spray equipment with water before product has started curing.

Packaging

4 litre and 15 litre plastic pails.

Shelf Life

Unopened pails can be stored for up to 12 months in a cool, dry and weatherproof environment.

SAFETY INSTRUCTIONS

For instructions on the safe use of WPA 360 please refer to the latest version of the Safety Data Sheet available from our website www.wpa-us.com.au.

Technical Data Sheet ISSUED AUGUST 2023

WARRANTY CONDITIONS

Bayset Pty Ltd trading as Waterproofing Products Australia (Bayset) offers a limited warranty in respect of this product, subject to certain terms and conditions set out in the warranty documentation which has been made available at www.bayset.com.au. Please contact Bayset directly to obtain a copy of the warranty documentation relevant to this product.

DISCLAIMER

The technical information and application advice given in this Technical Data Sheet is based on the present state of Bayset Pty Ltd's best scientific and practical knowledge and is intended to give a fair description of the product and its capabilities. As the information contained herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness, either expressed or implied, is given other than those required by law. In practice, the substrate and environmental conditions vary widely, making it essential for the user to determine the product's suitability for a particular application and that the product is not used beyond its physical limitations. The user is responsible for checking the suitability of products for their intended use.

***NOTE**

Field service where provided does not constitute supervisory responsibility. Suggestions made by Bayset Pty Ltd (trading as Waterproofing Products Australia) either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Waterproofing Products Australia, are responsible for carrying out procedures appropriate to a specific application. Australia either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Waterproofing Products Australia, are responsible for carrying out procedures appropriate to a specific application.

DOCUMENT CONTROL	
Product	WPA 360
Initial Issue	July 2016
Technical Amendment	August 2023
Author	SR

Technical Data Sheets are subject to change without notice.
For latest revision, check our website at www.wpa-us.com.au
This is a CONTROLLED document under WPA's Quality System.